

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 220 152 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
03.07.2002 Bulletin 2002/27

(51) Int Cl.7: **G06T 1/00**(21) Application number: **01310111.8**(22) Date of filing: **03.12.2001**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR**
Designated Extension States:
AL LT LV MK RO SI

(30) Priority: **07.12.2000 GB 0029865
07.12.2000 GB 0029869**

(71) Applicant: **SONY UNITED KINGDOM LIMITED
Weybridge KT13 0XW (GB)**

(72) Inventors:

- Pelly, Jason Charles
Reading, Berkshire RG6 4DU (GB)
- Tapson, Daniel
Basingstoke, Hampshire RG21 3PL (GB)
- Keating, Stephen Mark
Reading, Berkshire RG6 3AB (GB)

(74) Representative: **Pratt, Richard Wilson et al
D. Young & Co,
21 New Fetter Lane
London EC4A 1DA (GB)**

(54) Embedding data in material


(57) A spatial domain image I produced by a source 1 is combined with watermark data R_i to produce a spatial domain watermarked image I' . The watermarked image is produced by an embedder 3 according to the equation

$$C_i' = C_i + \alpha \cdot R_i$$

where C_i and C_i' are wavelet transform coefficients of the image, and α is a scaling factor, α is chosen so that the watermark is imperceptible in the image and to resist removal of the watermark by unauthorised processing. It is desirable that α has the smallest value which achieves that. If α is too big the watermark is perceptible in the image; if it is too small the mark may not survive processing of the image. α is determined from a trial decoding of the image I in a decoder 4. The decoding is that which would be used to decode the watermarked image I' . A value α' is produced by a calculator S3-S8, to which an offset value is added by an adder S9 to produce α . This produces values of α over the image, which are used to scale the data R_i so as to conceal the data. An image is one example of material to which the invention is applicable.

The step of producing modified coefficient values C_i may not use coefficients of magnitude greater than a threshold T and does not use corresponding information symbols R_i . Alternatively, a threshold T_{clip} may be set. The scaling factor α is calculated using clipped coeffi-

cient values and coefficients C_i of magnitude less than T_{clip} .

**FIG. 1****EP 1 220 152 A2**

Description

[0001] The present invention relates to embedding data in material.

[0002] "Material" as used herein means information material represented by information signals which includes at least one or more of image material, audio material. Image material is generic to still and moving images.

Steganography

[0003] Steganography is the embedding of data into material such as video material, audio material and data material in such a way that the data is imperceptible in the material.

[0004] Data may be embedded as a watermark in material such as video material, audio material and data material. A watermark may be imperceptible or perceptible in the material.

[0005] A watermark may be used for various purposes. It is known to use watermarks for the purpose of protecting the material against, or trace, infringement of the intellectual property rights of the owner(s) of the material. For example a watermark may identify the owner of the material.

[0006] Watermarks may be "robust" in that they are difficult to remove from the material. Robust watermarks are useful to trace the provenance of material which is processed in some way either in an attempt to remove the mark or to effect legitimate processing such as video editing or compression for storage and/or transmission. Watermarks may be "fragile" in that they are easily damaged by processing which is useful to detect attempts to remove the mark or process the material.

[0007] Visible watermarks are useful to allow e.g. a customer to view an image e.g. over the Internet to determine whether they wish to buy it but without allowing the customer access to the unmarked image they would buy. The watermark degrades the image and the mark is preferably not removable by the customer. Visible watermarks are also used to determine the provenance of the material into which they are embedded.

[0008] It is known to embed data in material. It is desirable to do that and allow the data to be removed from the material to avoid degrading the material. It is desirable to minimise any changes to the material needed to embed the data in it to avoid degrading the material. It is known to combine the data with the material, the data being scaled by a scaling factor which is chosen according to desired properties of the data when combined with the material. Those properties include one or more of: concealing the data in the material; making the data perceptible in the material; making the data, when embedded in the material, resistant to processing which, intentionally and unintentionally, removes or damages the embedded data.

[0009] According to a first aspect of the invention, there is provided a method of embedding data in material, the method comprising

combining a representation of the material with a function of the data and a scaling factor; wherein the scaling factor is generated as a function of a trial decoding of the material, the trial decoding comprising processing the material to recover data therefrom.

[0010] Thus the scaling factor can be chosen on the basis of an estimate of the result of a process (e.g. decoding) which will be performed on the combined material and data in practice so as to increase the likelihood that the data is recoverable from the material.

[0011] An embodiment of the first aspect of the invention further comprises the steps of:

combining, as a trial, a representation of the material with a function of the data and a trial scaling factor; and performing, as a trial, a predetermined process on the combined material and data;

wherein the scaling factor is generated as a function of a trial decoding of the processed combined material and data.

[0012] Thus the scaling factor can be chosen on the basis of an estimate of the result of a process (e.g. JPEG processing) which could be performed on the combined material and data in practice and which may damage the embedded data, so as to increase the likelihood that the data will not be damaged by such processing.

[0013] According to the first aspect of the invention, there is also provided a method of embedding data in material, the method comprising the steps of:

producing transform coefficients C_i representing a transform of the material;

producing a pseudo random symbol sequence (PRSS) having L symbols P_i of values $+1$ and -1 ;

calculating the correlation $S = \sum C_i P_i$, for $i=1$ to $i=L$; and

calculating modified coefficient values $C_i' = C_i + \alpha * P_i$, where α is calculated dependent on S and the value of the data bit to be embedded in the coefficient.

[0014] Preferably

$$\alpha = (\alpha' + \text{offset})$$

where $\alpha' + \text{offset}$ is a function of the data bit to be embedded in the coefficient, and the method comprises the step of calculating modified coefficient values

$$Ci' = Ci + (\alpha' + \text{offset}) \cdot Pi$$

where

$\alpha' = 0$ if S is positive and the data to be concealed is a bit of a first value,

$\alpha' = 0$ if S is negative and the data to be concealed is a bit of a second value,

and otherwise α' is a function of S such that $\sum Ci' \cdot Pi$ has the correct sign to represent the bit to be encoded.

[0015] It will be noted that the calculation of the correlation $S = \sum Ci \cdot Pi$, for $i=1$ to $i=L$ is a form of trial decoding as in the said first aspect and the scaling factor is chosen in dependence on that correlation.

[0016] A further aspect of the invention provides a computer program product arranged to carry out one of the afore-said methods when run on a computer.

[0017] The invention also provides corresponding apparatus in other aspects of the invention.

[0018] According to a second aspect of the present invention, there is provided a method of embedding data in material, comprising the steps of:

producing transform coefficients Ci of the material;

comparing the magnitudes of the coefficients with a threshold value T; and

producing, from the coefficients Ci and the said data modified, coefficient values Ci' which are modified by respective information symbols of a pseudo random symbol sequence modulated by the said data to be embedded;

wherein the said step of producing modified coefficient values does not use coefficients of magnitude greater than the said threshold T and does not use the corresponding information symbols.

[0019] The data is detected at a decoder by correlating a pseudo random symbol sequence with the material in which the data is embedded. The data is represented by the sign of the correlation function. By not using, during embedding, coefficients which have a value greater than the threshold, any changes necessary to alter the coefficients to achieve the appropriate sign of the correlation value to represent a bit of the concealed data are minimised.

[0020] According to the second aspect of the present invention, there is also provided a method for detecting data embedded in material, the detecting method comprising

receiving transform coefficients of the material;

comparing the magnitudes of the received coefficients with a threshold value T; and

correlating, the said coefficients with a respective symbols of a pseudo random symbol sequence to detect the said data, wherein the correlating step does not use coefficients of magnitude greater than the said threshold T and corresponding symbols of the pseudo random symbol sequence.

[0021] Thus the detecting method is complementary to the embedding method.

[0022] The second aspect of the invention also provides the following a), and b):

a) Apparatus for embedding data in material comprising a transformer for producing transform coefficients Ci of the material;

a comparator for comparing the magnitudes of the coefficients with a threshold value T; and

a combiner for producing, from the coefficients Ci and the said data, modified coefficient values Ci' which are modified by respective information symbols of a pseudo random symbol sequence modulated by the said data to be embedded, wherein the combiner does not use coefficients of magnitude greater than the said threshold T and does not use the corresponding information symbols;

b) Apparatus for detecting data embedded in material comprising an input for receiving transform coefficients of the material;

a comparator for comparing the magnitudes of the received coefficients with a threshold T; and

a correlator for correlating, the said coefficients with respective symbols of a pseudo random symbol sequence to detect the said data, wherein the correlation does not use coefficients of magnitude greater than the said threshold T and the corresponding symbols of the pseudo random symbol sequence.

[0023] Yet further, according to the second aspect of the invention, there is provided a method of detecting data embedded in material, the method comprising;

receiving transform coefficients of the material;

comparing the magnitudes of the received coefficients with a threshold T_{clip} ;

clipping, to a magnitude T_{clip} , the magnitude of coefficients of magnitude greater than the said threshold T_{clip} ; and

correlating the clipped and unclipped coefficients with a pseudo random symbol sequence to detect data embedded in the material.

[0024] Yet further, apparatus according of the second aspect for detecting data embedded in material, comprises;

an input for receiving transform coefficients C_i of the material;

a comparator for comparing the magnitudes of the received coefficients with a threshold T_{clip} ;

means for clipping, to a magnitude T_{clip} , the magnitude of coefficients of magnitude greater than the said threshold T_{clip} ; and

a correlator for correlating the clipped and unclipped coefficients with a pseudo random symbol sequence to detect data embedded in the material.

[0025] This further aspect of the invention may involve only the detecting method and operates independently of the embedding method. By clipping large value coefficients to a preset smaller value, such coefficients no longer dominate the value of the correlation function needed to decode the embedded data.

[0026] However, preferably, there is provided:

a) A method of embedding data in material, the method comprising

receiving transform coefficients C_i representing the material;

comparing the magnitudes of the said transform coefficients C_i with a threshold T_{clip} ;

clipping, to the magnitude T_{clip} , the magnitudes of those of the coefficients having a magnitude exceeding T_{clip} to produce clipped coefficients; and

producing modified coefficients C_i' of values dependent on a scaling factor and the data to be embedded, and the scaling factor is calculated using the said clipped coefficients and the coefficients C_i of magnitude less than T_{clip} .

b) Apparatus for embedding data in material, the apparatus comprising:

an input for receiving transform coefficients C_i representing the material;

a comparator for comparing the magnitudes of the said transform coefficients with a threshold T_{clip} ;

a clipper for clipping, to the magnitude T_{clip} , the magnitudes of those of the coefficients having a magnitude exceeding T_{clip} ; and

a processor for producing modified coefficients C_i' of values dependent on a scaling factor and the data to be embedded, and the scaling factor is calculated using the said clipped coefficients and the coefficients C_i of magnitude less than T_{clip} .

[0027] Thus by clipping large value coefficients to a smaller value such coefficients no longer dominate the value of the function used to calculate the scaling factor.

[0028] The invention also provides a computer program product arranged to carry out one of the aforesaid methods when run on a computer.

[0029] For a better understanding of the present invention, reference will now be made by way of example to the accompanying drawings in which:

Figure 1 is a schematic block diagram of an embodiment of a watermarking system according to the present invention;

Figure 2 is a schematic block diagram of another embodiment of a watermarking system according to the present invention;

Figure 3A is a schematic diagram of a wavelet transform showing the relationship of the symbols of a pseudo random symbol sequence to coefficients ;

Figure 3B is a flow diagram of calculations performed by the system of Figure 2;

Figure 4 is a schematic block diagram of an illustrative watermark decoding and removal system;

Figure 5 is a flow diagram of calculations performed by the watermark remover and decoder of Figure 4;

Figure 6 is a schematic block diagram of a further embodiment of a watermarking system according to the present invention;

Figures 7 to 10A are schematic block diagram of subsystems of the system of Figure 6;

Figures 10B and 10C are flow diagrams illustrating a process for calculating α ;

Figure 11A is a flow diagram of a modification, in accordance with the invention, of the flow diagram of Figure 3B;

Figure 11B is a diagram showing the relationship of coefficients C_i and symbols P_i of a pseudo random symbol sequence;

Figure 12 is a flow diagram of a modification, in accordance with the invention, of the flow diagram of Figure 5;

Figure 13 is a flow diagram of another modification, in accordance with the invention, of the flow diagram of Figure 5;

Figures 14 and 15 are diagrams explaining wavelet transforms; and

Figures 16 and 17 are diagrams showing a UMID and a data reduced UMID.

Overview

[0030] Referring to Figure 1, in the shown illustrative watermarking system, a spatial domain image I produced by a source 1 is combined with watermark data R_i to produce a spatial domain watermarked image I' . The watermarked image is produced by an embedder 3 according to the equation

$$C_i' = C_i + \alpha \cdot R_i$$

where C_i and C_i' are, for example, wavelet transform coefficients of the image, and α is a parameter which is also referred to herein as a scaling factor. α is chosen in this example so that the watermark is imperceptible in the image and to resist removal of the watermark by unauthorised processing. It is thus desirable that α has the smallest value which achieves that. If α is too big the watermark is perceptible in the image; if it is too small the mark may not survive processing of the image.

[0031] In accordance with this embodiment, α is determined from a trial decoding of the original *unmarked* image I in a decoder 4. The decoding is that which would be used to decode the watermarked image I' . A value α' is produced by a calculator S3-S8, to which an offset value is added by an adder S9 to produce α . This produces values of α over the image, which are used to scale the data R_i so as to conceal the data.

[0032] Figure 2 shows an example of the system of Figure 1 in which the calculation of α also encodes R_i . Figure 6 shows an example of the system of Figure 1 in which the trial decoding takes place after a trial processing of the image data by a process which is likely to be applied to the watermarked image.

[0033] The data R_i in the examples given below is derived from a UMID. UMIDs are described in the section *UMIDs* below. As mentioned above, and in the examples given below, the image is subjected to a wavelet transform. Wavelet transforms are briefly discussed in the section *Wavelets* below.

Figure 2

[0034] Referring to Figure 2, for the purposes of explanation, it is assumed that the wavelet transform applied to the original spatial domain image results in a transform having four sub-bands of level 1: see the section *Wavelets* below. For ease of explanation the following description will refer only to the upper horizontal sub-band, but it will be appreciated that the present invention can be applied to any sub-band and may be applied to a plurality of sub-bands. The coefficients of the wavelet transform are denoted by C_i where i is the i^{th} coefficient of a sequence of $J \times L$ coefficients where there are J bits of UMID data W_1 to W_J . As will become apparent the $J \times L$ coefficients correspond to symbols P_i of a Pseudo Random Symbol Sequence PRSS. Each UMID bit is embedded in L wavelet coefficients. Watermark data bit W_j is embedded in coefficients C_i for $i = (j-1)L + 1$ to jL .

[0035] In this example a UMID is produced as the watermark data by a UMID generator 6. In this example the watermark is imperceptible. The data of the UMID is combined with the wavelet coefficients C_i in an embedder 3 in the manner described in detail in the following text. The transformed image together with the watermark C_i' is subjected to an inverse wavelet transform T^{-1} , (5) to produce a spatial domain watermarked image I' .

[0036] The watermark is decoded and, optionally, removed from the watermarked image using the illustrative decoding and removal system of Figure 4.

Trial decoder 4

[0037] A trial decoder 4 comprises a generator 4_1 , a converter 4_2 , and a correlator S1. The generator 4_1 produces a pseudo random symbol sequence (PRSS) which is pseudo random because the sequence whilst appearing random can be reliably reproduced. The binary sequence has a length of $J \times L$ bits. The converter 4_2 converts the binary 1 and 0 to +1 and -1 respectively to produce a pseudo random symbol sequence (PRSS) P_i of values +1 and -1. The symbols of the PRSS are denoted herein by P_i , where i denotes the i^{th} symbol of the sequence which is $J \times L$ symbols long. The correlator S1 produces correlation values

$$S_j = \sum C_i \cdot P_i, \text{ where the sum is taken over the range } i = (j-1)L + 1 \text{ to } jL \text{ for each of } j=1 \text{ to } J. \text{ (See Figure 3A.)}$$

Calculation of α_j and embedding the UMID

[0038] There is one strength value α_j for each UMID bit W_j .

[0039] The calculation of α_j and the embedding of the UMID in the image operates in accordance with the flow diagram of Figure 3B. The embedder 3 calculates a function

$$C_i' = C_i + \alpha_j P_i \quad \text{for } i = (j-1)L + 1 \text{ to } jL \text{ for each of } j=1 \text{ to } J.$$

where C_i' is an i th wavelet coefficient modified to encoded a bit of watermarking data; and α_j is the scaling factor, the value of which depends on:

- a) the value 1 or 0 of a bit W_j of the UMID to be encoded in modified coefficient C_i' ; and
- b) the sign of the correlation value $S_j = \sum C_i P_i$, for $i = (j-1)L + 1$ to jL for each of $j=1$ to J , produced by the trial decoder 4; and
- c) the offset value, which is ± 1 in this example, so $\alpha_j = \alpha_j' + \text{offset}_j$.

[0040] The principle of operation is that a watermark bit $W_j=1$ is encoded as a positive correlation value and $W_j=0$ is encoded as a negative correlation value (or vice versa). α_j is chosen to ensure the value of a correlation $S_j' = \sum C_i'$ for $i = (j-1)L + 1$ to jL for each of $j=1$ to J , performed at the decoder has the correct sign to represent the value of bit W_j . If the correlation S_j performed at the encoder has the correct sign, then $\alpha_j' = 0$ otherwise α_j' is modified to ensure that the correlation $S_j' = \sum C_i' P_i$ performed at the decoder has the correct sign.

[0041] Thus referring to Figure 3B:-

A value $\alpha_j' = \alpha_j - \text{offset}_j$.

[0042] Step S1 (correlator S1 of Figure 2) calculates the correlation value $S_j = \sum C_i P_i$, where the sum is taken over the range $i = (j-1)L + 1$ to jL for a sequence $i = (j-1)L + 1$ to jL of coefficients C_i and PRSS bits P_i . (Note that 'symbols' P_i have values $+1$ and -1 to ensure that bits of value 0 produced by the generator 4 contribute to the value of S_j .) Step S1 is a trial decoding with a trial value of $\alpha_j = 0$.

[0043] Step S2 determines whether the bit W_j of the UMID generated by generator 6 is 1 or 0. It will be appreciated that the bit W_j is in effect encoded over L coefficients. If $W_j=1$ then steps S3 to S5 and S9+ are followed. These steps are implemented by blocks S3-S8 and S9 in figure 2.

[0044] Step S3 determines the sign of the correlation S_j . If the sign is positive and the bit W_j is 1 then

at step S4 $\alpha_j' = 0$.

[0045] If the sign determined at step S3 is negative but the bit $W_j = 1$ (which should be encoded by S_j positive), then

at step S5 $\alpha_j' = -S_j/(L-1)$.

[0046] At step S9+, the offset $+1$ is added to ensure that α_j is positive if $S_j=0$ and to increase robustness.. It should be noted that the offset is a signed value (± 1) in this example.

[0047] If $W_j=0$ then steps S6 to S8 and S9- are followed. These steps are implemented by blocks S3-S8 and S9 in figure 2.

[0048] Step S6 determines the sign of the correlation S_j . If the sign is negative and the bit W_j is 0 then

at step S7 $\alpha_j' = 0$.

[0049] If the sign determined at step S6 is positive but the bit $W_j = 0$ (which should be encoded by S_j negative), then

at step S8 $\alpha_j' = -S_j/(L-1)$.

[0050] At step S9 the offset -1 is added to ensure that α_j is negative if $S_j=0$ and to increase robustness. It should be noted that the offset is a signal value (-1) in this example.

[0051] At step S10 the value $C_i' = C_i + \alpha_j P_i$ is calculated for $i = (j-1)L + 1$ to jL .

[0052] The value $\alpha_j = -S_j/(L-1)$ is an example. The value α_j' could be $\alpha_j = -S_j/L$ as another example.

[0053] At step S9 an offset of +1 could be subtracted from α_j' .

Watermark Decoding and Removing System (Figures 4 and 5)

[0054] Referring to Figure 4, the watermark removing and decoding system has an input for receiving a spatial domain watermarked image I' from the system of Figure 1. The image may have been subject to image processing (not shown) between production by the system of Figure 1 and the receipt by the system of Figure 4.

[0055] The received image is transformed by a wavelet transformer 46 (T) to produce wavelet coefficients C_i' . The coefficients C_i' are provided to a synchroniser 8 which correlates the coefficients with a PRSS generated by a generator 10. The synchroniser 8 and the PRSS generator 10 carry out, in known manner, correlations with differing shifts of the PRSS relative to the coefficients to determine the position in the watermarked transformed image of the original PRSS produced at the watermarking system of Figure 1. Once synchronisation has been achieved the coefficients C_i' are correlated with the PRSS in another correlator 12 to produce the correlation value

$$S_j' = \sum C_i' \cdot P_i \text{ for } i = (j-1)L + 1 \text{ to } jL \text{ for each of } j=1 \text{ to } J.$$

where P_i has values +1 and -1.

[0056] The correlation value S_j' is provided to a decoder 14 and to a remover 16, the operations of which will be described with reference to the flow diagram of Figure 5. The decoder 14 extracts the UMID from the image. The watermark is removed by the remover 16. The resulting restored transformed image is subject to an inverse wavelet transform (T^{-1}) in an inverse transformer 18.

[0057] Referring to Figure 5, the synchronisation of the PRSS with the received transformed image occurs at step S12. At step S14, the correlation value

$$S_j' = \sum C_i' \cdot P_i \text{ for } i = (j-1)L + 1 \text{ to } jL.$$

is calculated over a length L of the PRSS.

[0058] At step S16, the sign of the value S_j' is determined. If S_j' is negative then the bit of the watermark, (the UMID in this example), is 0. If S_j' is positive the bit of the watermark is 1.

[0059] At step S18,

$$\alpha_j = S_j'/(L-1)$$

is calculated from S_j' . (This calculation may be an approximation because it assumes that $\sum C_i \cdot P_i = 0$)

[0060] At step S22, $C_i = C_i' - \alpha_j P_i$ is calculated for $i = (j-1)L + 1$ to jL .

[0061] If, in the embedding process, α_j is calculated as $-\frac{S_j}{L}$ at the step S5 or S8, then in the decoding process α_j' is calculated as S_j'/L at step S18.

Modifications.

a). Threshold on the values of C_i and C_i' (Figure 11A, Figure 12)

[0062] In a modification of the embodiment described above, the values of the coefficients C_i are compared (S40) with a threshold value Th_e at the embedder of Figure 2, and the values of the coefficients C_i' are compared S41 with a threshold value Th_d at the remover 16 of Figure 4 and also at the decoder 14 of Figure 4. If the value of a coefficient exceeds the threshold, that coefficient is not used (S42, S43) in establishing the correlation value S_j or S_j' . Th_e and Th_d may be equal, but it has been found that Th_d is preferably greater than Th_e .

[0063] By way of a simple example, assume that the PRSS has length $L=4$ and symbols P_1 to P_4 have values +1, -1, -1, and +1. Then referring to Table 1 three examples are shown.

Table 1

		P1 C1	P2 C2	P3 C3	P4 C4	Sj, α_j' Wj=0
	Pi	+1	-1	-1	+1	
Ex1	Ci	-2	-5	+1	-3	-1, 0
Ex2	Ci	-2	-25	+1	-3	+19, -19/3
Ex3	Ci	-2		+1	-3	-6, 0

Example 1 (Ex1)

[0064] The coefficients Ci have values shown. If the value of the bit Wj of the watermark to be encoded is 0 then according to Figure 3, Sj=-1 and so $\alpha_j' = 0$.

Example 2 (Ex2)

[0065] However if as shown in example 2 the coefficient C2 has a value -25 then Sj=+19 and $\alpha_j' = -19/3$. Large values of α_j' may cause the watermark to be perceptible when it should be imperceptible.

Example 3 (Ex3)

[0066] In accordance with an embodiment of the present invention, thresholds $+Th_e$ and $-Th_e$ are set. The magnitude of Th_e may be about 6 for the above example. In practice it is set empirically. Thus as shown in Table 1, the coefficient C2 is not used in the calculation of Sj, and also the corresponding symbol of the PRBS is also not used. As a result Sj=-6 and $\alpha_j' = 0$. Thus if the magnitude of a coefficient exceeds the threshold the coefficient is not used.

[0067] Now, referring to Figure 11A, in accordance with this embodiment, the following procedure takes place at the embedder before step S1 of Figure 3B.

[0068] At step S40, the magnitude of the coefficient value Ci is compared with the threshold Th_e . If the magnitude of Ci is greater than the threshold Th_e then at step S42 Ci is not used. Otherwise at step S44 Ci is used to calculate Ci' as described with reference to Figure 3B. Referring to Figure 11B, it will be recalled that each symbol Pi of the PRSS is associated with a coefficient Ci. When a coefficient Ci is not used because it exceeds the threshold, the corresponding symbol Pi generated by the generator 4 is also not used as indicated by the blocks Ci and Pi in Figure 11B.

b) Clipping coefficient values (Figure 13)

[0069] In an alternative modification, the values of the modified coefficients Ci' are clipped at the decoder of Figure 4 if they exceed (S80) a threshold value of magnitude Th_{clip} . Thus coefficient values greater than the threshold are reduced to a predetermined value e.g. Th_{clip} . For example referring to Table 1 Example 2, the coefficient C2 (-25) is clipped to say $+Th_{clip}$ e.g. -6 at the decoder. If $C_i > +Th_{clip}$, then Ci is set to $+Th_{clip}$ (step S84).

[0070] If $Th_{clip} = 6$ is only an example and in practice may have other values set by experiment.

[0071] Such clipping may or may not be performed also at the embedder of Figure 2.

[0072] In the embedder shown in Figure 2 it is not performed. However, in another embodiment, the procedure of Figure 13 may be applied prior to step S1 in Figure 3B.

[0073] The clipping is performed only for the purpose of calculating the parameter α_j . The coefficients Ci to which α_j , Pi is added do not have clipped values.

Limiting α'

[0074] The value of α' may be limited to be within a present range determined by upper and lower bounds.

Trial processing and decoding- Figure 6

[0075] Referring to Figure 6, an unmarked spatial domain image I is applied to an embedder 60. An example of the embedder is shown in Figure 8. The embedder calculates

$$Ci' = Ci + \alpha_{Tj} Ri \text{ for } i = (j-1)L + 1 \text{ to } jL \text{ for each of } j=1 \text{ to } J.$$

where: Ci is a wavelet transform coefficient of the image; Ri is a watermarking symbol formed by combining a PRSS of JxL bits Pi with watermark data Wj . Symbol Ri has a value + or - 1; $\alpha_{t,j}$ is a trial value of the scaling factor for UMID (or watermark) data bit Wj . In this example $\alpha_{t,j}$ is initialised to 1. Figure 7 shows an example of a subsystem, for producing Ri .

[0076] The embedder also includes an inverse transformer which produces a spatial domain watermarked image Iw .

[0077] The image Iw is processed by a processor 62 to produce a processed spatial domain image Ip . The processor 62 is chosen to process the image according to a process which the watermarked image is likely to encounter in use, and/or a process which may be applied to the image to deliberately remove or damage the watermark. JPEG processing using DCT transforms is a process which is known to be potentially damaging to some watermarks.

[0078] A decoder 64, an example of which is shown in Figure 9, decodes the processed image Ip . The decoder may extract the watermark data Wj . The decoder produces correlation values

$$Sip,j' = \sum Cip.Pi \text{ for } i = (j-1)L + 1 \text{ to } jL \text{ for each of } j=1 \text{ to } J.$$

where Cip are wavelet coefficients of the processed image Ip and the sum is calculated over a length L of a PRSS having JxL bits Pi .

[0079] A calculator 66 calculates a new value of α_j based on the magnitude of Sip,j to produce new trial values of α_{t+nj} which is used as a new value in the trial embedder 60. n is the number of iterations used to calculate a final value α_{t+nj} which is applied to an embedder 69. $n = 0, 1, 2$. Several iterations may be used. Preferably the number of iterations is limited to a predetermined number, e.g. 4, because the process 62 may be non-linear (JPEG processing is non-linear) and it is then unlikely that the iterations will converge to steady values of $\alpha_{t,j}$.

[0080] Examples of (a) the calculator 66 and (b) the embedder 69 are shown in Figures 10 and 8 respectively.

Calculating Ri , Figure 7.

[0081] A PRSS generator 71 produces a PRSS having JxL bits Pi . A UMID generator 72 produces a UMID having bits Wj . In a modulator 73, each bit Wj of the UMID modulates, and is thus spread over, an L bit sequence of the PRSS. A data converter 74 converts the binary values 1 and 0 at the output of the modulator to produce symbols Ri of value +1 and -1 respectively.

Embedder 60 and 69,- Figure 8.

[0082] The embedder of Figure 8 comprises a wavelet transformer 82 which produces the wavelet coefficients Ci and an inverse transformer 85. A multiplier 84 calculates $\alpha_{t+nj}.Ri$. An adder 83 adds $\alpha_{t+nj}.Ri$ to Ci to produce.

$$Ci' = Ci + \alpha_{t+nj}.Ri \text{ for } i = (j-1)L + 1 \text{ to } jL \text{ for each of } j=1 \text{ to } J.$$

[0083] Thus each coefficient Ci is modified by a value of α associated with that coefficient and by one symbol Ri .

[0084] Unlike the example of Figures 2 and 3, Ri is a symbol stream comprising the PRSS modulated by the data to be embedded, and α is an unsigned magnitude.

Decoder 64-Figure 9

[0085] The decoder has a wavelet transformer 91 which produces wavelet coefficients Cip from the processed image Ip . A synchroniser 92 operating in known manner shifts the phase of the PRSS produced by a PRSS generator 93 so that it is in phase with the PRSS in the image Ip . A data converter 94 converts the PRSS values Pi to +1 and -1. A correlator calculates a correlation value

$$Sip,j = \sum Cip.Pi \text{ for } i = (j-1)L + 1 \text{ to } jL \text{ for each of } j=1 \text{ to } J.$$

[0086] A decoder 96 determines the values of the data bits Wj from the sign of the correlation values Sip,j .

Calculating α -Figures 10A, 10B and 10C

[0087] Referring to Figure 10A, new values of $\alpha_{t+1,j}$ are calculated by adding an offset to a basic fixed value $\alpha_{t,j}$ in an adder 99. The offsets are produced by an offset generator 95. The generator responds to an offset control value produced by a processor 97. The processor controls the offset and thus the values of $\alpha_{t+1,j}$ in dependence on the correlation values Sip,j .

[0088] Figures 10B and 10C illustrate examples of the operation of the processor.

[0089] Referring to Figure 10B, the correlation values Sip,j are compared at step S30 with the corresponding symbols W_j . The correlation values Sip,j are positive and negative, a positive value indicates a symbol 1 and a negative value a symbol 0, (if the values Sip are unchanged by the processing in processor 62). If the signs of Sip,j correctly represent W_j then the magnitude of Sip,j is compared with an upper threshold Th . If $|Sip,j| > Th$ then the value of α_j is reduced for the next iteration $\alpha_{t+1,j}$. If $|Sip,j|$ is not greater than the threshold α_j either remains unchanged for the next iteration $\alpha_{t+1,j}$ or is used as the final value of $\alpha_{t,j}$.

[0090] If the sign of Sip,j indicates the incorrect value for W_j , then α_j is increased for the next iteration $\alpha_{t+1,j}$.

[0091] Referring to Figure 10C, at step S40 a value $(Sip,j)/L$ is calculated from Sip,j . That is the average correlation value over L symbols. That value is used as $\alpha_{t+1,j}$ for the next iteration. Preferably $\alpha_{t+1,j}$ is compared with an upper threshold Th at step S42. If $\alpha_{t+1,j}$ exceeds Th , then $\alpha_{t+1,j}$ is reduced. Otherwise it is compared (S46) with a lower threshold TL . If $\alpha_{t+1,j}$ is less than TL , $\alpha_{t+1,j}$ is increased (S48) otherwise it is unchanged (S49).

Modifications.Other transforms

[0092] Whilst the invention has been described by way of example with reference to Wavelet transforms, it may be used with other transforms for example DCT.

Other material

[0093] Whilst the invention has been described by way of example with reference to material comprising images, e. g. video material, it may be applied to other material, for example audio material and data material.

Other Watermark data.

[0094] Whilst the invention has been described by way of example with reference to UMIDs as the watermark data, it may be used with other data as the watermark.

Wavelets

[0095] Wavelets are well known and are described in for example "A Really Friendly Guide to Wavelets" by C Valens, 1999 and available at <http://perso.wanadoo.fr/polyvalens/clemens/wavelets/wavelets.html>.

[0096] Valens shows that the discrete wavelet transform can be implemented as an iterated filter bank as used in sub-band coding, with scaling of the image by a factor of 2 at each iteration.

[0097] Thus referring to Figure 12, a spatial domain image is applied to a set of high pass HP and low pass LP filters. At level 1, the first stage of filtering, the image is filtered horizontally and vertically and, in each direction, scaled down by a factor of 2. In level 2, the low pass image from level 1 is filtered and scaled in the same way as in level 1. The filtering and scaling may be repeated in subsequent levels 3 onwards.

[0098] The result is shown schematically in Figure 11. Figure 11 is a representation normal in the art. At level one the image is spatially filtered into four bands: the lower horizontal and vertical band, lH_1, lV_1 ; the upper horizontal band hH_1, lV_1 ; the upper vertical band lH_1, hV_1 ; and the upper horizontal and vertical band, hH_1, hV_1 . At level 2, the lower horizontal and vertical band, lH_1, lV_1 is filtered and scaled into the lower horizontal and vertical band, lH_2, lV_2 ; the upper horizontal band hH_2, lV_2 ; the upper vertical band lH_2, hV_2 ; and the upper horizontal and vertical band, hH_2, hV_2 . At level 3 (not shown in Figure 11), the lower horizontal and vertical band, lH_2, lV_2 is further filtered and scaled.

UMIDs

[0099] The UMID or Unique Material Identifier is described in SMPTE Journal March 2000. Referring to Figure 13, an extended UMID is shown. It comprises a first set of 32 bytes of basic UMID and a second set of 32 bytes of signature metadata.

[0100] The first set of 32 bytes is the basic UMID. The components are:

- A 12-byte Universal Label to identify this as a SMPTE UMID. It defines the type of material which the UMID identifies and also defines the methods by which the globally unique Material and locally unique Instance numbers are created.
- A 1-byte length value to define the length of the remaining part of the UMID.
- A 3-byte Instance number which is used to distinguish between different 'instances' of material with the same Material number.
- A 16-byte Material number which is used to identify each clip. Each Material number is the same for related instances of the same material.

[0101] The second set of 32 bytes of the signature metadata as a set of packed metadata items used to create an extended UMID. The extended UMID comprises the basic UMID followed immediately by signature metadata which comprises:

- An 8-byte time/date code identifying the time and date of the Content Unit creation.
- A 12-byte value which defines the spatial co-ordinates at the time of Content Unit creation.
- 3 groups of 4-byte codes which register the country, organisation and user codes

[0102] Each component of the basic and extended UMIDs will now be defined in turn.

The 12-byte Universal Label

[0103] The first 12 bytes of the UMID provide identification of the UMID by the registered string value defined in table 1.

Table 1:

Specification of the UMID Universal Label		
Byte No.	Description	Value (hex)
1	Object Identifier	06h
2	Label size	0Ch
3	Designation: ISO	2Bh
4	Designation: SMPTE	34h
5	Registry: Dictionaries	01h
6	Registry: Metadata Dictionaries	01h
7	Standard: Dictionary Number	01h
8	Version number	01h
9	Class: Identification and location	01h
10	Sub-class: Globally Unique Identifiers	01h
11	Type: UMID (Picture, Audio, Data, Group)	01, 02, 03, 04h
12	Type: Number creation method	XXh

[0104] The hex values in table 1 may be changed: the values given are examples. Also the bytes 1-12 may have designations other than those shown by way of example in the table. Referring to the Table 1, in the example shown byte 4 indicates that bytes 5-12 relate to a data format agreed by SMPTE. Byte 5 indicates that bytes 6 to 10 relate to "dictionary" data. Byte 6 indicates that such data is "metadata" defined by bytes 7 to 10. Byte 7 indicates the part of the dictionary containing metadata defined by bytes 9 and 10. Byte 10 indicates the version of the dictionary. Byte 9 indicates the class of data and Byte 10 indicates a particular item in the class.

[0105] In the present embodiment bytes 1 to 10 have fixed preassigned values. Byte 11 is variable. Thus referring to Figure 14, and to Table 1 above, it will be noted that the bytes 1 to 10 of the label of the UMID are fixed. Therefore they may be replaced by a 1 byte 'Type' code T representing the bytes 1 to 10. The type code T is followed by a length code L. That is followed by 2 bytes, one of which is byte 11 of Table 1 and the other of which is byte 12 of Table 1, an

instance number (3 bytes) and a material number (16 bytes). Optionally, the material number may be followed by the signature metadata of the extended UMID and/or other metadata.

[0106] The UMID type (byte 11) has 4 separate values to identify each of 4 different data types as follows:

- 5 '01h' = UMID for Picture material
- '02h' = UMID for Audio material
- '03h' = UMID for Data material
- '04h' = UMID for Group material (i.e. a combination of related essence).

10 [0107] The last (12th) byte of the 12 byte label identifies the methods by which the material and instance numbers are created. This byte is divided into top and bottom nibbles where the top nibble defines the method of Material number creation and the bottom nibble defines the method of Instance number creation.

Length

15 [0108] The Length is a 1-byte number with the value '13h' for basic UMIDs and '33h' for extended UMIDs.

Instance Number

20 [0109] The Instance number is a unique 3-byte number which is created by one of several means defined by the standard. It provides the link between a particular 'instance' of a clip and externally associated metadata. Without this instance number, all material could be linked to any instance of the material and its associated metadata.

[0110] The creation of a new clip requires the creation of a new Material number together with a zero Instance number. Therefore, a non-zero Instance number indicates that the associated clip is not the source material. An Instance number is primarily used to identify associated metadata related to any particular instance of a clip.

Material Number

30 [0111] The 16-byte Material number is a non-zero number created by one of several means identified in the standard. The number is dependent on a 6-byte registered port ID number, time and a random number generator.

Signature Metadata

35 [0112] Any component from the signature metadata may be null-filled where no meaningful value can be entered. Any null-filled component is wholly null-filled to clearly indicate a downstream decoder that the component is not valid.

The Time-Date Format

40 [0113] The date-time format is 8 bytes where the first 4 bytes are a UTC (Universal Time Code) based time component. The time is defined either by an AES3 32-bit audio sample clock or SMPTE 12M depending on the essence type.

[0114] The second 4 bytes define the date based on the Modified Julian Data (MJD) as defined in SMPTE 309M. This counts up to 999,999 days after midnight on the 17th November 1858 and allows dates to the year 4597.

The Spatial Co-ordinate Format

45 [0115] The spatial co-ordinate value consists of three components defined as follows:

- Altitude: 8 decimal numbers specifying up to 99,999,999 metres.
- Longitude: 8 decimal numbers specifying East/West 180.00000 degrees (5 decimal places active).
- 50 • Latitude: 8 decimal numbers specifying North/South 90.00000 degrees (5 decimal places active).

[0116] The Altitude value is expressed as a value in metres from the centre of the earth thus allowing altitudes below the sea level.

55 [0117] It should be noted that although spatial co-ordinates are static for most clips, this is not true for all cases. Material captured from a moving source such as a camera mounted on a vehicle may show changing spatial co-ordinate values.

Country Code

[0118] The Country code is an abbreviated 4-byte alpha-numeric string according to the set defined in ISO 3166. Countries which are not registered can obtain a registered alpha-numeric string from the SMPTE Registration Authority.

Organisation Code

[0119] The Organisation code is an abbreviated 4-byte alpha-numeric string registered with SMPTE. Organisation codes have meaning only in relation to their registered Country code so that Organisation codes can have the same value in different countries.

User Code

[0120] The User code is a 4-byte alpha-numeric string assigned locally by each organisation and is not globally registered. User codes are defined in relation to their registered Organisation and Country codes so that User codes may have the same value in different organisations and countries.

Claims

1. A method of embedding data in material, the method comprising
 combining a representation of the material with a function of the data and a scaling factor; wherein
 the scaling factor is generated as a function of a trial decoding of the material,
 the trial decoding comprising processing the material to recover data therefrom.
2. A method according to claim 1, wherein the step of combining involves modulating a pseudo random symbol
 sequence with the said data and the trial decoding comprises the step of correlating a pseudo random symbol
 sequence with the said representation of the material, and the scaling factor is generated in dependence on the
 result of the correlation.
3. A method according to claim 1 or 2, further comprising:
 combining, as a trial, a representation of the material with a function of the data and a trial scaling factor; and
 performing, as a trial, a predetermined process on the combined material and data;
 wherein the scaling factor is generated as a function of a trial decoding of the processed combined material
 and data.
4. A method of embedding data bits in material, the method comprising the steps of:
 producing transform coefficients C_i representing a transform of the material;
 producing a pseudo random symbol stream having L symbols P_i of values +1 and -1;
 calculating a correlation $S = \sum C_i \cdot P_i$, for $i=1$ to $i=L$; and
 calculating modified coefficient values $C'_i = C_i + \alpha \cdot P_i$, where α is calculated dependent on S and the value
 of the data bit to be embedded in the coefficient.
5. A method according to claim 4 wherein

$$\alpha = (\alpha' + \text{offset})$$
 where $\alpha' + \text{offset}$ is a function of the data bit to be embedded in the coefficient,
 $\alpha' = 0$ if S is positive and the data to be concealed is a symbol of a first value,
 $\alpha' = 0$ if S is negative and the data to be concealed is a symbol of a second value, and
 otherwise α' is a function of S such that $\sum C'_i \cdot P_i$ has the correct sign to represent the symbol to be encoded.
6. A method according to claim 5, wherein the first value is "1" and the second value is "0".

7. A method according to claim 4, 5 or 6 wherein the said function of S is

$$\alpha' = -S/(L-1) \text{ or } \alpha' = -S/L.$$

8. A method according to claim 4, 5, 6 or 7, wherein the magnitude of the offset is greater than or equal to zero.

9. A method according to claim 8, wherein the magnitude of the offset is one.

10. A method according to any preceding claim, wherein the said coefficients are coefficients of a wavelet transform of the material.

11. A method according to any preceding claim wherein the data to be embedded includes a UMID.

12. A method of removing data from material, which data has been embedded by the method of any one of claims 4 to 11, the method comprising the steps of:

calculating the correlation $S' = \sum C_i' \cdot P_i$ for $i=1$ to L where P_i are the bits of the PRSS and have values +1 and -1;
calculating α_r as a function of S' ; and
calculating $C_i = C_i' - \alpha_r \cdot P_i$ to recover the unmodified coefficients C_i .

13. A method according to claim 12, wherein $\alpha_r = S'/(L-1)$ or $\alpha_r = (S'/L)$.

14. A method according to claim 12 or 13, further comprising deriving the symbols of the concealed data from S' , where if S' is positive a symbol is of the first value and if S' is negative a symbol is of the second value.

15. A method according to claim 12, 13 or 14, comprising the step of generating and synchronizing a reference pseudo random symbol sequence with the pseudo random symbol sequence of the embedded data.

16. A computer program product arranged to carry out the method of any preceding claim when run on a computer.

17. Apparatus for embedding data in material, the apparatus comprising:

a combiner for combining a representation of the material with a function of the data and a scaling factor;
a decoder for decoding, as a trial, the material to recover data therefrom; and
a generator for generating the scaling factor as a function of the trial decoding of the material.

18. Apparatus according to claim 17, wherein:

the combiner includes a modulator for modulating a pseudo random symbol sequence with the said data;
the trial decoder comprises a correlator for correlating the pseudo random binary sequence with the said material; and
the scaling factor generator is arranged to generate the scaling factor in dependence on the result of the correlation.

19. Apparatus according to claim 17 or 18, wherein the combiner is arranged to combine, as a trial, a representation of the material with a function of the data and a trial scaling factor;
and further comprising:

a processor for performing, as a trial, a predetermined process on the combined material and data;

wherein the scaling factor is generated as a function of a trial processing of the processed combined material and data so as to recover the said data.

20. Apparatus for embedding data in material, the apparatus comprising:

a transformer for producing transform coefficients C_i representing a transform of the material;
a generator for producing a pseudo random symbol stream having L bits P_i ;

an input for receiving symbol representing the data to be concealed; and
a data embedder arranged to
calculate a correlation $S = \sum C_i \cdot P_i$, for $i=1$ to $i=L$ and
calculate modified coefficient values $C_i' = C_i + \alpha \cdot P_i$, where α is calculated dependent on S and the value of
the data bit to be embedded in the coefficient.

21. Apparatus according to claim 20 wherein

$$\alpha = (\alpha' + \text{offset})$$

where $\alpha' + \text{offset}$ is a function of the data bit to be embedded in the coefficient, and the apparatus is arranged to
calculate modified coefficient values $C_i' = C_i + (\alpha' + \text{offset}) \cdot P_i$ where
 $\alpha' = 0$ if S is positive and the data to be concealed is a bit of a first value,
 $\alpha' = 0$ if S is negative and the data to be concealed is a bit of a second value, and
otherwise α' is a function of S such that $\sum C_i' \cdot P_i$ has the correct sign to represent the bit to be encoded.

22. Apparatus according to claim 21, wherein the first value is "1" and the second value is "0".

23. Apparatus according to claim 21 or 22 wherein $\alpha = -S/(L-1)$ or $-S/L$

24. Apparatus according to claim 20, 21, 22 or 23, wherein the offset is greater than or equal to zero.

25. Apparatus according to claim 25 wherein the offset = 1.

26. Apparatus according to any one of claims 20 to 25, wherein the coefficients are coefficients of a wavelet transform
of the material.

27. Apparatus according to any one of claims 19 to 24 comprising a generator for generating a UMID as the said data
to be concealed.

28. Apparatus for removing data from material, which data has been concealed by the apparatus of any one of claims
20 to 27, the apparatus comprising:

a generator for generating a PRSS; and
a calculator for calculating
the correlation $S' = \sum C_i' \cdot P_i$ for $i=1$ to L where P_i are the bits of the PRSS,
a value α_r dependent on S' , and
a coefficient value $C_i = C_i' - \alpha_r \cdot P_i$ to recover the unmodified coefficients C_i .

29. Apparatus according to claim 26, wherein $\alpha_r = S/(L-1)$ or (S/L) .

30. Apparatus according to claim 28 or 29, further comprising a decoder for deriving the bits of the concealed data
from the correlation value S' , where if S' is positive a bit of the data has a first value and if S' is negative a bit of
the data has a second value.

31. Apparatus according to claim 28, 29 or 30, comprising a synchronizer for synchronizing the generated PRSS with
the PRSS of the embedded data.

32. A method of embedding data in material, comprising the steps of:

producing transform coefficients C_i of the material;
comparing the magnitudes of the coefficients with a threshold value T ; and
producing, from the coefficients C_i and the said data, modified coefficient values C_i' which are modified by
respective information symbols of a pseudo random symbol sequence modulated by the said data to be em-
bedded;

wherein the said step of producing modified coefficient values does not use coefficients of magnitude greater

than the said threshold T and does not use the corresponding information symbols.

33. A method according to claim 32, wherein the modified coefficients

5

$$Ci' = Ci + \alpha \cdot Pi$$

where $\alpha \cdot Pi$ is an information symbol modulated by the data to be embedded, α being a scaling factor.

10

34. A method according to claim 33, wherein α is dependent on the data.

35. A method according to claim 33, wherein α is of fixed value.

36. A method according to claim 32, wherein the modified coefficients

15

$$Ci' = Ci + \alpha \cdot Ri$$

where Ri is an information symbol Pi modulated by the data, and α is a scaling factor.

20

37. A method according to claim 32, 33, 34, 35 or 36, wherein the said transform is a wavelet transform.

38. A method according to claim 32, 33, 34, 35 or 36, wherein the said transform is a spatial frequency transform.

25

39. A method for detecting data embedded in material, the detecting method comprising
receiving transform coefficients of the material;
comparing the magnitudes of the received coefficients with a threshold value T; and
correlating, the said coefficients with a respective symbols of a pseudo random symbol sequence to detect
the said data, wherein the correlating step does not use coefficients of magnitude greater than the said threshold
T and corresponding symbols of the pseudo random symbol sequence.

30

40. A method according to claim 39, further comprising removing the said data from the said received coefficients not
using coefficients of magnitude greater than said threshold T.

35

41. A method of detecting data embedded in material, the method comprising;
receiving transform coefficients of the material;
comparing the magnitudes of the received coefficients with a threshold Tclip;
clipping, to a magnitude Tclip, the magnitude of coefficients of magnitude greater than the said threshold
Tclip; and
correlating the clipped and unclipped coefficients with a pseudo random symbol sequence to detect data
embedded in the material.

40

42. A method according to claim 41, further comprising removing data from said clipped and unclipped coefficients.

45

43. A method comprising embedding data according to any one of claims 32 to 40 and a method of detecting the data
according to claim 10 or 11.

44. A method of embedding data in material, the method comprising
receiving transform coefficients Ci representing the material;
comparing the magnitudes of the said transform coefficients Ci with a threshold Tclip;
clipping, to the magnitude Tclip, the magnitudes of those of the coefficients having a magnitude exceeding
Tclip to produce clipped coefficients; and
producing modified coefficients Ci' values dependent on a scaling factor and the data to be embedded, and
the scaling factor is calculated using the said clipped coefficients and the coefficients Ci of magnitude less than Tclip.

50

45. A computer program product arranged to carry out the method of any one of claims 32 to 44 when run on a computer.

46. Apparatus for embedding data in material, comprising:

a transformer for producing transform coefficients C_i of the material;
 a comparator for comparing the magnitudes of the coefficients with a threshold value T ; and
 a combiner for producing, from the coefficients C_i and the said data, modified coefficient values C_i' which are
 modified by respective information symbols of a pseudo random symbol sequence modulated by the said data
 to be embedded, wherein the combiner does not use coefficients of magnitude greater than the said threshold
 T and does not use the corresponding information symbols.

47. Apparatus according to claim 46, wherein the combiner is arranged to produce modified coefficients

$$C_i' = C_i + \alpha \cdot P_i$$

where $\alpha \cdot P_i$ is an information symbol modulated by the data to be embedded, α being a scaling factor.

48. Apparatus according to claim 47, wherein α is dependent on the data.

49. Apparatus according to claim 47, wherein α is of fixed value.

50. Apparatus according to claim 46, wherein the combiner is arranged to produce coefficients

$$C_i' = C_i + \alpha \cdot R_i$$

where R_i is an information symbol P_i modulated by the data, and α is a scaling factor.

51. Apparatus according to claim 50, comprising a pseudo random sequence generator and a modulator for modulating the pseudo random sequence with the said data.

52. Apparatus according to claim 46, 47, 48, 49, 50 or 51, wherein the said transformer is a wavelet transformer.

53. Apparatus according to claim 46, 47, 48, 49, 50 or 51, wherein the said transformer produces a spatial frequency transform of the said material.

54. Apparatus for detecting data embedded in material, the detecting apparatus comprising
 an input for receiving transform coefficients of the material;
 a comparator for comparing the magnitudes of the received coefficients with a threshold T ; and
 a correlator for correlating the said coefficients with respective symbols of a pseudo random symbol sequence to detect the said data, wherein the correlation does not use coefficients of magnitude greater than the said threshold T and the corresponding symbols of the pseudo random symbol sequence.

55. Apparatus according to claim 54, further comprising a data remover for removing data from the receiving coefficients, the remover omitting coefficients of magnitude greater than the said threshold T .

56. Apparatus for detecting data embedded in material, comprising;
 an input for receiving transform coefficients C_i' of the material;
 a comparator for comparing the magnitudes of the received coefficients with a threshold T_{clip} ;
 a clipper for clipping, to a magnitude T_{clip} , the magnitude of coefficients of magnitude greater than the said threshold T ; and
 a correlator for correlating the clipped and unclipped coefficients with a pseudo random symbol sequence to detect data embedded in the material.

57. Apparatus according to claim 56, further comprising a remover for removing data from the clipped and unclipped coefficients.

58. Apparatus for embedding data in material, the apparatus comprising:

an input for receiving transform coefficients C_i representing the material;
 a comparator for comparing the magnitudes of the said transform coefficients with a threshold T_{clip} ;

a clipper for clipping, to the magnitude T_{clip} , the magnitudes of those of the coefficients having a magnitude exceeding T_{clip} ; and
a processor for producing modified coefficients C_i' values dependent on a scaling factor and the data to be embedded, and the scaling factor is calculated using the said clipped coefficients and the coefficients C_i of magnitude less than T_{clip} .

59. A system comprising embedding apparatus according to any one of claims 46 to 53 and detecting apparatus according to claim 54, 55, 56 or 57.

60. A method or apparatus according to any preceding claim wherein the said data comprises a UMID.

61. A method or apparatus according to any one of claims 32 to 60, wherein the said material comprises video material.

62. A method or apparatus according to any one of claims 32 to 61, wherein the said material comprises audio material.




FIG. 1




FIG. 2





FIG. 3A






FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10A




FIG. 10B




FIG. 10C




FIG. 11A




FIG. 11B




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 220 152 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
24.11.2004 Bulletin 2004/48

(51) Int Cl.7: **G06T 1/00**

(43) Date of publication A2:
03.07.2002 Bulletin 2002/27

(21) Application number: **01310111.8**(22) Date of filing: **03.12.2001**

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR
Designated Extension States:
AL LT LV MK RO SI

(30) Priority: **07.12.2000 GB 0029865**
07.12.2000 GB 0029869

(71) Applicant: **SONY UNITED KINGDOM LIMITED**
Weybridge KT13 0XW (GB)

(72) Inventors:
• **Pelly, Jason Charles**
Reading, Berkshire RG6 4DU (GB)
• **Tapson, Daniel**
Basingstoke, Hampshire RG21 3PL (GB)
• **Keating, Stephen Mark**
Reading, Berkshire RG6 3AB (GB)

(74) Representative: **Pratt, Richard Wilson et al**
D Young & Co
120 Holborn
London EC1N 2DY (GB)

(54) Embedding data in material


(57) A spatial domain image I produced by a source 1 is combined with watermark data R_i to produce a spatial domain watermarked image I' . The watermarked image is produced by an embedder 3 according to the equation

$$C_i' = C_i + \alpha \cdot R_i$$

where C_i and C_i' are wavelet transform coefficients of the image, and α is a scaling factor, α is chosen so that the watermark is imperceptible in the image and to resist removal of the watermark by unauthorised processing. It is desirable that α has the smallest value which achieves that. If α is too big the watermark is perceptible in the image; if it is too small the mark may not survive processing of the image. α is determined from a trial decoding of the image I in a decoder 4. The decoding is that which would be used to decode the watermarked image I' . A value α' is produced by a calculator S3-S8, to which an offset value is added by an adder S9 to produce α . This produces values of α over the image, which are used to scale the data R_i so as to conceal the data. An image is one example of material to which the invention is applicable.

The step of producing modified coefficient values C_i may not use coefficients of magnitude greater than a

threshold T and does not use corresponding information symbols R_i . Alternatively, a threshold T_{clip} may be set. The scaling factor α is calculated using clipped coefficient values and coefficients C_i of magnitude less than T_{clip} .

**FIG. 1****EP 1 220 152 A3**



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 01 31 0111

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	MILLER M L ET AL: "Informed embedding: exploiting image and detector information during watermark insertion" PROCEEDINGS INTERNATIONAL CONFERENCE ON IMAGE PROCESSING, vol. 3, 10 September 2000 (2000-09-10), pages 1-4, XP010529388 * sections 2,3 *	1,17,60	G06T1/00
X	COX I J ET AL: "WATERMARKING AS COMMUNICATIONS WITH SIDE INFORMATION" PROCEEDINGS OF THE IEEE, IEEE, NEW YORK, US, vol. 87, no. 7, July 1999 (1999-07), pages 1127-1141, XP000914457 ISSN: 0018-9219 * figures 3,6 * * page 1134, left-hand column, paragraphs 1,2 *	1,17,60	
X	SU P-C ET AL: "BLIND DIGITAL WATERMARKING FOR CARTOON AND MAP IMAGES" PROCEEDINGS OF THE SPIE, SPIE, BELLINGHAM, VA, US, vol. 3657, 25 January 1999 (1999-01-25), pages 296-306, XP000949150 ISSN: 0277-786X * section 3.1 * * figure 1 *	41,42, 44,45, 56-62	TECHNICAL FIELDS SEARCHED (Int.Cl.7) G06T H04N
Y	EP 1 043 687 A (CANON KK) 11 October 2000 (2000-10-11) * figures 1,10 * * page 2, line 27 - line 58 * * page 3, line 19 - line 30 * * page 7, line 16 - line 21 *	4,12,16, 20,60,61	
-/--			
The present search report has been drawn up for all claims			
Place of search Berlin		Date of completion of the search 27 September 2004	Examiner dos Santos, L
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date O : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

EPO FORM 1503 03.82 (P4/C01)



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 01 31 0111

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
Y	WEN-NUNG LIE ET AL: "Robust image watermarking on the DCT domain" IEEE INTERNATIONAL SYMPOSIUM ON CIRCUITS AND SYSTEMS. EMERGING TECHNOLOGIES FOR THE 21ST CENTURY. IEEE CAT NO.00CH36353. PRESSES POLYTECH. UNIV. ROMANDES LAUSANNE, SWITZERLAND, vol. 1, 28 May 2000 (2000-05-28), pages 228-231 vol.1, XP002298071 ISBN: 0-7803-5482-6 * section 3 *	4,12,16, 20,60,61	TECHNICAL FIELDS SEARCHED (Int.Cl.7)
Y	DUG-RYUNG KIM ET AL: "A robust data embedding using perceptual adaptive watermark" CIRCUITS AND SYSTEMS. IEEE APCCAS 1998. THE 1998 IEEE ASIA-PACIFIC CONFERENCE ON CHIANGMAI, THAILAND. PISCATAWAY, NJ, USA, 24 November 1998 (1998-11-24), pages 415-418, XP010319342 ISBN: 0-7803-5146-0 * page 416, right-hand column, line 40 - line 45 *	32-40, 43, 45-55,59	
Y	DUGAD R ET AL: "A scheme for joint watermarking and compression of video" PROCEEDINGS INTERNATIONAL CONFERENCE ON IMAGE PROCESSING (CAT. NO.00CH37101) IEEE PISCATAWAY, NJ, USA, vol. 2, 10 September 2000 (2000-09-10), pages 80-83 vol.2, XP010529928 ISBN: 0-7803-6297-7 * section 2 *	32-40, 43, 45-55,59	
The present search report has been drawn up for all claims			
Place of search Berlin		Date of completion of the search 27 September 2004	Examiner dos Santos, L
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

EPO FORM 1503 03/82 (P04C01)



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 01 31 0111

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
P,A	BARNI M ET AL: "Watermark embedding: hiding a signal within a cover image" IEEE COMMUNICATIONS MAGAZINE, USA, vol. 39, no. 8, August 2001 (2001-08), pages 102-108, XP002288675 ISSN: 0163-6804 * section "Additive, Non-Additive, and Substitution Watermarks" * * section "Informed Embedding" *	1-3,10, 11, 16-19, 27,60-62	
A	WILKINSON J H ET AL: "TOOLS AND TECHNIQUES FOR GLOBALLY UNIQUE CONTENT IDENTIFICATION" SMPTE JOURNAL, SMPTE INC. SCARSDALE, N.Y., US, vol. 109, no. 10, October 2000 (2000-10), pages 795-799, XP000969315 ISSN: 0036-1682 * figure 1 *	1-3,10, 11, 16-19, 27,60-62	
A	MACQ B: "LOSSLESS MULTIREOLUTION TRANSFORM FOR IMAGE AUTHENTICATING WATERMARKING" PROCEEDINGS OF THE EUROPEAN SIGNAL PROCESSING CONFERENCE, vol. 4, 8 September 2000 (2000-09-08), pages 1973-1976, XP008032665 * section 2 *	41,42, 44,45, 56-62	TECHNICAL FIELDS SEARCHED (Int.Cl.7)
The present search report has been drawn up for all claims			
Place of search Berlin		Date of completion of the search 27 September 2004	Examiner dos Santos, L
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principles underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

EPO FORM 1503 03/82 (P04C01)



European Patent
Office

Application Number
EP 01 31 0111

CLAIMS INCURRING FEES

The present European patent application comprised at the time of filing more than ten claims.

- ☐ Only part of the claims have been paid within the prescribed time limit. The present European search report has been drawn up for the first ten claims and for those claims for which claims fees have been paid, namely claim(s):
- ☐ No claims fees have been paid within the prescribed time limit. The present European search report has been drawn up for the first ten claims.

LACK OF UNITY OF INVENTION

The Search Division considers that the present European patent application does not comply with the requirements of unity of invention and relates to several inventions or groups of inventions, namely:

see sheet B

- ☒ All further search fees have been paid within the fixed time limit. The present European search report has been drawn up for all claims.
- ☐ As all searchable claims could be searched without effort justifying an additional fee, the Search Division did not invite payment of any additional fee.
- ☐ Only part of the further search fees have been paid within the fixed time limit. The present European search report has been drawn up for those parts of the European patent application which relate to the inventions in respect of which search fees have been paid, namely claims:
- ☐ None of the further search fees have been paid within the fixed time limit. The present European search report has been drawn up for those parts of the European patent application which relate to the invention first mentioned in the claims, namely claims:



European Patent
Office

LACK OF UNITY OF INVENTION
SHEET B

Application Number
EP 01 31 0111

The Search Division considers that the present European patent application does not comply with the requirements of unity of invention and relates to several inventions or groups of inventions, namely:

1. claims: 1-3,10,11,16-19,27,60,61,62

claims 1-3,10 (when depending on claims 1-3),11,16 (when carrying out the method of 1-3,10,11),17-19,27 (when depending on claim 19),60 (when depending on claims 1-3,10,11,16,17-19,27),61 (when depending on claims 1-3,10,11,16-19,27,60),62 (when depending on claims 1-3,10,11,16-19,27,60,61)
Increasing the robustness of a detected watermark against the deterioration caused in the watermarked image by a compression / decompression process.

2. claims: 4-9,10-16,20-31,60,61,62

claims 4-9,10-11 (when depending on claims 4-9),12-15,16 (when carrying out the method of claims 4-9,10-15),20-26,27 (when depending on claims 20-24),28-31,60 (when depending on claims 4-9,10-16,20-31),61 (when depending on claims 4-9,10-16,20-31,60),62 (when depending on claims 4-9,10-16,20-31,60,61)
Increase the imperceptibility of a watermark represented by a random sequence at the embedding stage.

3. claims: 32-40,43,45-55,59,60,61,62

claims 32-40,43 (when depending on claims 32-40),45 (when depending on claims 32-40,43),46-55,59 (when depending on claims 46-55),60 (when depending on claims 32-40,43,45-55),61 (when depending on claims 32-40,43,45-55,60),62 (when depending on claims 32-40,43,45-55,60,61)
Increasing the speed of a watermark embedding device.

4. claims: 41,42,44,45,56-62

claims 41,42,44,45 (when depending on claims 41,42,44),56,57,58,59 (when comprising apparatus claim 56,57),60 (when depending on 41,42,44,56-59),61 (when depending on 41,42,44,56-60),62 (when depending on 41,42,44,56-61)
Avoiding overflow errors when embedding a watermark.

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 31 0111

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

27-09-2004

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 1043687	A	11-10-2000	FR 2792152 A1	13-10-2000
			FR 2792153 A1	13-10-2000
			FR 2795585 A1	29-12-2000
			EP 1043687 A1	11-10-2000
			JP 2000350014 A	15-12-2000

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82